

TOVO



BURLEIGH SHORT

DESCRIPTION	Surface mounted downlight with short barrel
CODES	3450
FINISHES	White, Black, Copper, Brass, Stainless Steel, Aged Copper, Aged Brass, Custom
COLOUR TEMP	2700K, 3000K
BEAM ANGLE	24, *38, 60
	36 (GU10)
CRI	≥90
LUMEN OUTPUT	527Lm
	650Lm (GU10)
WATTAGE	5W
	7,5W (GU10)
FIXTURE VOLTAGE	24V DC Constant Voltage
	240V AC (GU10)
DIMMING	Based On Driver and Voltage Selection
DRIVER	Remote Driver Required for 24V DC Selection
	GU10 Lamp Provided for 240V AC Selection
DRIVER OPTIONS	Non-Dim, Phase, Touch, DALI
IP RATING	IP66



BLACK



WHITE



COPPER



BRASS



STAINLESS
STEEL



CUSTOM






AGED
COPPER



AGED
BRASS



INGRESS
IP66



Notes:
*38 degree beam angle as a standard

BURLEIGH SHORT

MANUFACTURING OPTIONS

FIXTURE

CODE	FINISH	CCT	BEAM ANGLE	VOLTAGE
3450	WH - White	27 - 2700K	24 - 24° Narrow	24V - 24V DC
	BLK - Black	30 - 3000K	38 - 38° Medium	
	CU - Copper		60 - 60° Wide	
	BR - Brass			
	SS - Stainless Steel			
	AC - Aged Copper			
	AB - Aged Brass			
CF - Custom Finish				

DRIVER

DIMMING
ND - Non-Dim
PH - Phase Dim
TH - Touch Dim
DA - DALI

CCT	BEAM ANGLE	VOLTAGE	DIMMING
27 - 2700K	36 - 36° Medium	240V - 240V AC	ND - Non-Dim
30 - 3000K		(GU10)	PH - Phase Dim

Example Code: 3450_CU_27_38_24V
