



TOVO



AIRLIE

DESCRIPTION	Mini Adjustable Garden Spike
CODES	4590
FINISHES	Black, Copper, Brass, Stainless Steel, Aged Copper, Aged Brass, Custom
COLOUR TEMP	2700K, 3000K
BEAM ANGLE	38
CRI	≥90
LUMEN OUTPUT	420Lm
WATTAGE	4W
FIXTURE VOLTAGE	24V DC Constant Voltage
DIMMING	Based On Driver Selection
DRIVER	Remote Driver Required
DRIVER OPTIONS	Non-Dim, Phase, Touch, DALI
IP RATING	IP66

Notes:
All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



MANUFACTURING OPTIONS

F I X T U R E						D R I V E R
CODE	FINISH	SPIKE	CCT	BEAM ANGLE	VOLTAGE	DIMMING
4590	BLK - Black	S3 - 300mm	27 - 2700K	38 - 38° Medium	24V - 24V DC	ND - Non-Dim
	CU - Copper	S6 - 600mm	30 - 3000K			PH - Phase Dim
	BR - Brass	S9 - 900mm				TH - Touch Dim
	SS - Stainless Steel	SC - Custom Length				DA - DALI
	AC - Aged Copper					
	AB - Aged Brass					
	CF - Custom Finish					

Example Code: 4590_CU_S6_27_38_24V

Notes:
Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.

ACCESSORIES

