

## C41 CT

DESCRIPTION Fixed garden spike with glass diffuser

CODES 2022

FINISHES Black, Copper, Brass, Stainless Steel, Custom,

Aged Copper, Aged Brass

COLOUR TEMP 2700K, 3000K
BEAM ANGLES 60, \*38, 24
CRI ≥90
LUMEN OUTPUT 550Lm
WATTAGE 5W

FIXTURE VOLTAGE 24V DC Constant Voltage

DIMMING Based On Driver Selection

DRIVER Remote Driver Required

DRIVER OPTIONS Non-Dim, Phase, Touch, DALI

IP RATING IP66

Notes:

All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



















## MANUFACTURING OPTIONS

FIXTURE						DRIVER
CODE	FINISH	SPIKE	ССТ	BEAM ANGLE	VOLTAGE	DIMMING
2022	BLK - Black	<b>S3</b> - 300mm	<b>27</b> - 2700K	<b>24</b> - 24° Narrow	24V - 24V DC	ND - Non-Dim
	CU - Copper	<b>\$6</b> - 600mm	<b>30</b> - 3000K	<b>38</b> - 38° Medium		PH - Phase Dim
	BR - Brass	<b>S9</b> - 900mm		<b>60</b> - 60° Wide		TH - Touch Dim
	SS - Stainless Steel	SC - Custom Length				DA - DALI
	AC - Aged Copper					
	AB - Aged Brass					
	CF - Custom Finish					

Example Code: 2022\_CU\_\$6\_27\_38\_24V

Notes:
\*38 degree beam angle as standard.
Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.

## ACCESSORIES

