

TOVO



LONG REEF

DESCRIPTION	Up/Down Wall Light
CODES	1600
FINISHES	White, Black, Copper, Brass, Stainless Steel, Custom
COLOUR TEMP	2700K, 3000K
BEAM ANGLE	60, 38, 24
	36 (GU10)
CRI	≥90
LUMEN OUTPUT	1100Lm (550Lm per head 24V DC) 1300Lm (650Lm per head GU10)
WATTAGE	10W (5W per head 24V DC) 15W (7.5W per head GU10)
FIXTURE VOLTAGE	24V DC Constant Voltage 240V AC (GU10)
DIMMING	Based On Driver and Voltage Selection
DRIVER	Remote Driver Required for 24V DC Selection GU10 Lamp Provided for 240V AC Selection
DRIVER OPTIONS	Non-Dim, Phase, Touch, DALI
IP RATING	IP66

Notes:
All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



WHITE



BLACK



COPPER



BRASS




STAINLESS
STEEL



CUSTOM



INGRESS
IP66



LONG REEF

MANUFACTURING OPTIONS

FIXTURE						DRIVER
CODE	FINISH	BACK PLATE	CCT	BEAM ANGLE	VOLTAGE	DIMMING
1600	WH - White	SB - Standard Base	27 - 2700K	24 - 24° Narrow	24V - 24V DC	ND - Non-Dim
	BLK - Black	FRN - Flat Round	30 - 3000K	38 - 38° Medium		PH - Phase Dim
	CU - Copper			60 - 60° Wide	TH - Touch Dim	
	BR - Brass				DA - DALI	
	SS - Stainless Steel					
	CF - Custom Finish					

BACK PLATE	CCT	BEAM ANGLE	VOLTAGE	DIMMING
SB - Standard Base	27 - 2700K	36 - 36° Medium	240V - 240V AC	ND - Non-Dim
FRN - Flat Round	30 - 3000K		(GU10)	PH - Phase Dim
FRE - Flat Rectangular				

Example Code: 1600_CU_FSQ_27_38_24V

Notes:
 240V AC Fixture are only available with GU10 lamps.
 Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.

BACK PLATES



Notes:
 All screws provided for installation into different materials.