

TOVO




NEWPORT

DESCRIPTION	Adjustable Garden Spike
CODES	1300
FINISHES	Black, Copper, Brass, Stainless Steel, Custom
COLOUR TEMP	2700K, 3000K
BEAM ANGLES	*60, 38, 24
CRI	≥90
LUMEN OUTPUT	676Lm
WATTAGE	8W
FIXTURE VOLTAGE	24V DC Constant Voltage
DIMMING	Based On Driver Selection
DRIVER	Remote Driver Required
DRIVER OPTIONS	Non-Dim, Phase, Touch, DALI
IP RATING	IP66

Notes:

*60 degree beam angle as standard.

All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



INGRESS
IP66

ROTATION
360°

TILT
160°



BLACK



COPPER



BRASS



STAINLESS
STEEL



CUSTOM

NEWPORT

MANUFACTURING OPTIONS

FIXTURE						DRIVER
CODE	FINISH	SPIKE	CCT	BEAM ANGLE	VOLTAGE	DIMMING
1300	BLK - Black	S3 - 300mm	27 - 2700K	24 - 24° Narrow	24V - 24V DC	ND - Non-Dim
	CU - Copper	S6 - 600mm	30 - 3000K	38 - 38° Medium		PH - Phase Dim
	BR - Brass	S9 - 900mm		60 - 60° Wide		TH - Touch Dim
	SS - Stainless Steel	SC - Custom length				DA - DALI
	CF - Custom Finish					

Example Code: **1300_CU_S6_27_38_24V**

Notes:

*60 degree beam angle as standard.

Phase dimmable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.

ACCESSORIES

