

## PORT DOUGLAS

DESCRIPTION Large Trafficable In Ground Up Light

CODES 4908

FINISHES White, Black, Copper, Brass, Stainless Steel, Custom

COLOUR TEMP 2700K, 3000K BEAM ANGLE 13, \*24 CRI ≥90 1265 Lm LUMEN OUTPUT

WATTAGE 18W

FIXTURE VOLTAGE 24V DC Constant Voltage

DIMMING Based On Driver and Voltage Selection DRIVER Remote Driver Required for 24V DC Selection

DRIVER OPTIONS Non-Dim, Phase, Touch, DALI

IP RATING IP66

\*24 degree beam angle as a standard All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



















## PORT DOUGLAS

## MANUFACTURING OPTIONS

FIXTURE					DRIVER
CODE	FINISH	ССТ	BEAM ANGLE	VOLTAGE	DIMMING
4908	BLK - Black	<b>27</b> - 2700K	<b>13</b> - 13° Narrow	24V - 24V DC	ND - Non-Dim
	CU - Copper	<b>30</b> - 3000K	<b>24</b> - 24° Narrow		PH - Phase Dim
	BR - Brass				TH - Touch Dim
	SS - Stainless Steel				DA - DALI
	CF - Custom Finish				

Example Code: 4908\_CU\_27\_24\_24V