



KS88

DESCRIPTION : POWDERCOATED SURFACE MOUNT DOWNLIGHT

CODE : 4388

COLOURS : BLACK, WHITE

COLOUR TEMPERATURE : 2700K, 3000K

CRI : 92

LUMENS : 580lm

INPUT VOLTAGE : 24V_DC

WATTAGE : 9.5W



BEAM ANGLE : 60°, 38°, 24°, 15°, 7°

DIMMABLE : YES
PHASE, AUTOMATION, DALI

DRIVER : REMOTE

IP RATING : IP20

CUT OUT : N.A






PHOTOMETRY

MODEL **KS88 DOWNLIGHT WITH BT LED v6.8 LAMP**

NOMINAL POWER	9.5W	LIGHT OUTPUT RATIO	100%
RATED VOLTAGE	240V	CIE CLASS	DIRECT
NOMINAL FLUX	762.63 LM	UP	0.1%
LAMPS INSIDE	1	DOWN	99.9%
IMAX	961.2 CD	EFFICIENCY	80.20 LM/W

CANDELA DISTRIBUTION

VERTICAL ANGLE	HORIZONTAL ANGLE									ZONAL LUMENS
	0°	45°	90°	135°	180°	225°	270°	315°		
10	874.6	869.8	889.0	910.6	903.4	880.9	868.1	873.3	88.14	
20	642.0	651.6	670.3	688.0	685.9	664.4	636.9	623.0	306.3	
30	344.5	372.7	396.5	402.9	400.5	371.4	337.4	323.5	539.3	
40	119.1	143.3	158.9	137.0	157.9	138.2	114.9	109.8	690.0	
50	28.31	23.87	22.48	21.02	21.31	21.61	25.16	27.12	740.1	
60	12.20	9.888	8.162	6.467	6.803	8.035	9.791	10.81	753.8	
70	5.147	3.866	2.539	2.309	1.503	2.602	3.876	5.090	759.1	
80	2.693	1.743	0.8730	0.9571	0.0791	0.6308	1.661	2.543	761.7	
90	0.0007	0	0	0	0	0	0	0	762.2	
100	0	0	0	0	0	0	0	0	762.2	
110	0	0	0	0	0	0	0	0	762.2	
120	0	0	0	0	0	0	0	0	762.2	
130	0	0	0	0	0	0	0	0	762.2	
140	0	0	0	0	0	0	0	0	762.2	
150	0	0	0	0	0.3966	0.3158	0.3955	0.3978	762.3	
160	0.1583	0.2353	0.1582	0.1577	0.6331	0.7098	0.7118	0.6365	762.4	
170	0.6297	0.6255	0.5518	0.4799	0.6331	0.7098	0.7118	0.6365	762.6	
180	0.7122	0.7912	0.8700	0.7161	0.6331	0.7098	0.7118	0.6365	762.6	




AVERAGE BEAM ANGLE (50%): 52.2°
 UNIT: CD
 — C0 180°, 52.4°
 — C90 270°, 52.1°

VERTICAL ANGLE	HORIZONTAL ANGLE	
	0	90
85	573	37
80	610	198
75	626	265
70	592	292
65	671	318
60	959	642
55	1270	949
50	1732	1375
45	3441	3736

COEFFICIENTS OF UTILISATION (%)

CEILING	80%			70%			50%			30%			10%			0
	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
WALL	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
FLOOR	20%			20%			20%			20%			20%			0
RCR 0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1	1.11	1.08	1.06	1.08	1.06	1.04	1.04	1.03	1.01	1.01	.99	.98	.97	.96	.95	.93
2	1.03	.99	.95	1.01	.97	.94	.98	.95	.92	.95	.92	.90	.92	.90	.88	.87
3	.96	.91	.87	.94	.90	.86	.92	.88	.85	.89	.86	.83	.87	.84	.82	.81
4	.90	.84	.80	.88	.83	.79	.86	.82	.78	.84	.80	.77	.82	.79	.76	.75
5	.84	.78	.74	.83	.77	.73	.81	.76	.73	.79	.75	.72	.78	.74	.71	.70
6	.79	.73	.68	.78	.72	.68	.76	.71	.68	.75	.71	.67	.74	.70	.67	.65
7	.74	.68	.64	.73	.68	.64	.72	.67	.63	.71	.66	.63	.70	.66	.63	.61
8	.70	.64	.60	.69	.64	.60	.68	.63	.59	.67	.63	.59	.66	.62	.59	.58
9	.66	.60	.56	.66	.60	.56	.65	.59	.56	.64	.59	.56	.63	.59	.55	.54
10	.63	.57	.53	.62	.57	.53	.61	.56	.53	.60	.56	.53	.60	.55	.52	.51

Flux out : 474.8 lm



BODY

THIS IS A TWO PIECE ALUMINIUM DOWNLIGHT WITH A SIMPLE AND EFFECTIVE INSTALLATION. THE BACKPLATE IS REMOVEABLE FROM THE MAIN BODY SO IT IS ABLE TO BE INSTALLED ONTO THE CEILING WITH THE SCREWS, THE LAMPHOLDER WITH LAMP IS THEN ATTACHED. THE CYLINDRICAL BODY HAS THREAD AT THE TOP, WHICH IS THEN SCREWED ONTO THE BACKPLATE IN THE CEILING

LAMP

BRIGHTTEK LED LAMP WITH DIMMABLE A 36V 250m LED DRIVER. THE BT LAMP IS AVAILABLE IN A WARM WHITE 2700K AND 3000K. 4000K IS AVAILABLE ON CUSTOM REQUEST.

INSTALLATION

RECESSED DOWNLIGHT.

POWER SUPPLY

24V LED FLEX & PLUG DRIVE

