

# TOVO

## BURLEIGH

DESCRIPTION	Surface Mounted Downlight
CODES	3452
FINISHES	White, Black, Copper, Brass, Stainless Steel, Custom
COLOUR TEMP	2700K, 3000K
BEAM ANGLE	*60, 38, 24
	36 (GU10)
CRI	≥90
LUMEN OUTPUT	676Lm
	650Lm (GU10)
WATTAGE	8W
	7,5W (GU10)
FIXTURE VOLTAGE	24V DC Constant Voltage
	240V AC (GU10)
DIMMING	Based On Driver and Voltage Selection
DRIVER	Remote Driver Required for 24V DC Selection
	GU10 Lamp Provided for 240V AC Selection
DRIVER OPTIONS	Non-Dim, Phase, Touch, DALI
IP RATING	IP66

Notes:  
\*60 degree beam angle as a standard  
All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.



WHITE



BLACK



COPPER






BRASS



STAINLESS  
STEEL



CUSTOM



INGRESS  
IP66

# BURLEIGH

---

## MANUFACTURING OPTIONS

---

FIXTURE					DRIVER
CODE	FINISH	CCT	BEAM ANGLE	VOLTAGE	DIMMING
3452	WH - White	27 - 2700K	24 - 24° Narrow	24V - 24V DC	ND - Non-Dim
	BLK - Black	30 - 3000K	38 - 38° Medium		PH - Phase Dim
	CU - Copper		60 - 60° Wide		TH - Touch Dim
	BR - Brass				DA - DALI
	SS - Stainless Steel				
CF - Custom Finish					
		CCT	BEAM ANGLE	VOLTAGE	DIMMING
		27 - 2700K	36 - 36° Medium	240V - 240V AC	ND - Non-Dim
		30 - 3000K		(GU10)	PH - Phase Dim

Example Code: **3452\_CU\_27\_38\_24V**

Notes:  
\* 240V AC Fixture are only available with Integral Back Plates. A non-dimmable AC to DC driver is provided inside the Back Plate.  
Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.