

## TWEED

DESCRIPTION Mini Surface Mounted Downlight

CODES 3455

FINISHES White, Black, Copper, Brass, Stainless Steel, Custom

COLOUR TEMP 2700K, 3000K

BEAM ANGLE 38
CRI ≥90
LUMEN OUTPUT 420Lm
WATTAGE 4W

FIXTURE VOLTAGE 24V DC Constant Voltage

DIMMING Based On Driver and Voltage Selection

DRIVER Remote Driver Required
DRIVER OPTIONS Non-Dim, Phase, Touch, DALI

IP RATING IP66

Notes:

All data stipulated are nominal values based on 2700K with accuracy of +/- 5%.





BRASS













## TWEED

## MANUFACTURING OPTIONS

FIXTURE					DRIVER
CODE	FINISH	ССТ	BEAM ANGLE	VOLTAGE	DIMMING
3452	WH - White	<b>27</b> - 2700K	<b>38</b> - 38° Medium	24V - 24V DC	ND - Non-Dim
	BLK - Black	<b>30</b> - 3000K			PH - Phase Dim
	CU - Copper				TH - Touch Dim
	BR - Brass				DA - DALI
	SS - Stainless Steel				
	CF - Custom Finish				

Example Code: **3455\_CU\_27\_38\_24V** 

Notes:

\* 240V AC Fixture are only available with Integral Back Plates. A non-dimmable AC to DC driver is provided inside the Back Plate.

Phase dimable drivers are not recommended for 24V DC fixtures due to possible flickering, but can be provided upon request.